

# ROD EASE

*This product is a superior lubricant for HDD, coring, and rotary drilling.*

## **Typical Physical Properties**

Physical appearance.....	Dark brown liquid
Specific gravity .....	0.887
pH.....	7.0–7.5
Boiling point .....	572°F (>300°C)
Freezing point.....	-77°F (-25°C)
Flash point.....	554°F (290°C)

## **Applications**

ROD EASE\* lubricant mixes instantly and is not affected by water quality. For this product to deliver rod protection and reduce torque after drilling has started, consideration must be given to the number of rods and the amount of fluid in the hole. Treatment can require dosing the system with several pails of lubricant. Established maintenance levels are required after initial dosage and treatment. Normal treatment levels are 1 to 2% of fluid volume or 1 to 2 pints (0.473 to 0.946 L) per 100 gal (378.5 L) of drilling fluid. The dosage amount should be increased if the penetration rate decreases, torque increases, or the run length decreases indicating poor cutting.

## **Advantages**

- Reduces torque
- Prevents rust and scale
- Environmentally safe
- Increases penetration rates
- Extends bit and mud motor life
- Increases mud motor efficiency
- Reduces wear on rods and equipment
- Maximizes rig potential and steering control
- Enhances the effectiveness of powdered drilling-fluid additives

ROD EASE lubricant is based on an environmentally safe technology that has proven effective in lubricating downhole consumables. This product has produced both bit-life and penetration increases of more than 25% during drilling operations. Because ROD EASE lubricant reduces torque and drag, the operator can use the drill rig to its full potential, meaning thrusts and pulls are at a minimum, and steering control is precise.

Tests performed in the M-I SWACO laboratory in Houston confirm the effects of ROD EASE lubricant.



*Customer-focused, solutions-driven*

---

### ***Limitations***

None

### ***Toxicity and Handling***

Bioassay information is available upon request.

Handle as an industrial chemical, wearing protective equipment and observing the precautions described in the Material Safety Data Sheets (MSDS).

### ***Packaging and Storage***

ROD EASE lubricant is packaged in 5-gal (18.9-L) buckets and 55-gal (208.2-L) drums.

Store in a well-ventilated area away from sources of heat or ignition.

This information is supplied solely for informational purposes and M-I SWACO makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

©2007 M-I LLC All rights reserved.  
\*Mark of M-I LLC  
HPB.1802.0706.R3 (E)



HDD Mining & Waterwell Group  
5950 North Course Drive, Suite 431  
Houston, TX 77072  
Tel: 832-295-2564  
Fax: 832-351-4131  
[www.drilling-fluids.com](http://www.drilling-fluids.com)  
E-mail: [hdd@miswaco.com](mailto:hdd@miswaco.com)